

Features

- Easy to install and replace
- Clean looking
- High brightness
- Energy Saving



Applications


- Spot lighting in commercial usage
- Replacement for halogen lamp



PAR20 PAR30 PAR38



	PAR20	PAR30	PAR38
Diameter:	2.5in/64mm	3.75in/95mm	4.76in/121mm
Height:	3.7in/88.4mm	4.4in/112mm	5.21in/132mm
Carton size:	355*213*325mm	330*220*250 mm	405*270*310mm
Q'ty/ctn	45 pcs	12 pcs	12 pcs



Item Code	Description	Wattage	Color Temp	Input Voltage	Output Lumen	Equiv.wattage	CRI	Beam Angle	Dimmable
DX-PAR20-US-500-03	LED7PAR20/DIM/8XX/NFLXX/03	7W	2700-5000K	120V	500LM	50W	80	25°/30°/36°/40°	YES
DX-PAR30LN-650LM-03	LED10PAR30/DIM/8XX/NFLXX/03	10W	2700-5000K	120V	650LM	50W	80	25°/30°/40°	YES
DX-PAR30LN-800LM-03	LED12PAR30/DIM/8XX/NFLXX/03	12W	2700-5000K	120V	800LM	75W	80	25°/30°/40°	YES
DX-PAR38-1050LM-03	LED14PAR38/DIM/8XX/NFLXX/03	14W	2700-5000K	120V	1050LM	90W	80	25°/40°	YES
DX-PAR38-1300LM-03	LED17PAR38/DIM/8XX/NFLXX/03	17W	2700-5000K	120V	1300LM	120W	80	25°/40°	YES
DX-PAR30LN-1050LM-03	LED14PAR30/8XX/NFLXX/03	14W	2700-5000K	120-277V	1050LM	90W	80	25°/30°/40°	NO
DX-PAR38-2300LM	LED28PAR38/8XX/NFLXX	28W	2700-5000K	120-277V	2300LM	250W	80	25°/40°	NO

