


产品特点

- 比传统卤素灯节能85%
- 平滑, 整洁
- 颜色均匀, 一致
- 防碎
- 易于替换
- 符合E26/E27的基座插座标准

欧规 A60



直径:	2.36in/60mm	外箱尺寸:	195*176*305mm
高度:	4.33in/110mm	装箱数量:	12 pcs

技术型号	编码	瓦数	色温	输入电压赫兹	输出流明	替代传统灯瓦数	显色指数	发光角度	是否调光
DX-A60-9W-250D	LED9A60/NON DIM/250D	9W	2700-6500K	200~240V 50HZ	800LM	60W	80	250°	NO
DX-A60-9W-250D	LED9A60/DIM/250D	9W	2700-6500K	200~240V 50HZ	800LM	60W	80	250°	YES
DX-A60-6W-250D	LED6A60/NON DIM/250D	6W	2700-6500K	200~240V 50HZ	450LM	40W	80	250°	NO
DX-A60-6W-250D	LED6A60/DIM/250D	6W	2700-6500K	200~240V 50HZ	450LM	40W	80	250°	YES
DX-A60-9W-160D	LED9A60/NON DIM/160D	9W	2700-6500K	200~240V 50HZ	800LM	60W	80	160°	NO
DX-A60-9W-160D	LED9A60/DIM/160D	9W	2700-6500K	200~240V 50HZ	800LM	60W	80	160°	YES
DX-A60-6W-160D	LED6A60/NON DIM/160D	6W	2700-6500K	200~240V 50HZ	450LM	40W	80	160°	NO
DX-A60-6W-160D	LED6A60/DIM/160D	6W	2700-6500K	200~240V 50HZ	450LM	40W	80	160°	YES

应用领域

- 完美匹配各种电器设备, 比如台灯, 吊灯, 电风扇, 室内装饰灯具, 室外灯具等。

